# SECTION 12: ECOLOGICAL INFORMATION

Toxicity:

Aquatic Toxicity: No further relevant information available. Persistence and Degradability: No further relevant information available. Behavior in Environmental Systems: Bioaccumulative Potential: No further relevant information available. Mobility in Soil: No further relevant information available. General Information: Do not flush into surface water or sanitary sewer system.

# SECTION 13: DISPOSAL CONSIDERATIONS

#### Product:

*Recommendation:* Use proper landfill disposal or incineration in accordance with local, state and federal regulations.

# Uncleaned Packaging:

Recommendation: Disposal must be made according to official regulations.

# SECTION 14: TRANSPORT INFORMATION

Land Transport ADR/RID	
and GGVS/GGVE (Germany):	UN 1173 ETHYLACETAT, 3, II
Sea transport IMDG:	UN 1173 ETHYLACETAT, 3, II
Air Transport ICAO-TI and IATA-DGR:	UN 1173 ETHYLACETATE, 3, II

# SECTION 15: REGULATORY INFORMATION

Classification According to EC-Guidelines: The product is a medical device according to EC-directive 93/42 EEC. Chemical Safety Assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: OTHER INFORMATION

Changes Compared With the Previous Version: Adaptation according to 1907/2006/EG, Article 31.

# Prepared by: Peter G. Jordan

The above information is based on our present day knowledge and relates solely to the safety requirements of the product. The data does not signify any warranty with regards to the product's properties. However, users of the product should satisfy themselves that the information given is sufficient and correct for their specific circumstances of use.



# INSTRUCTIONS FOR USE

Glisten Provisional Resin Glaze is a light-cure, one component varnish which cures hard, and without any smear layer. Glisten is for coating surfaces of temporary crowns or bridges based on acrylic and bisacrylic systems.

# PROPERTIES:

The special properties of Glisten are its fully dry surface without leaving a smear layer after light polymerization, its hard, high gloss, and more abrasion-resistant surface.

The resistance of the covered crown and/or bridge will even be improved against solvation by some denture cleaning agents and against food deposits and plaque.

# APPLICATION:

- Remove the provisional material smear layer with a suitable solvent (e.g.: alcohol).
- Apply a thin layer of Glisten without inclusion of air bubbles with a brush onto the dull and dry provisional restorative surface.
- 3. Light-cure the Glisten coating immediately after application:
- Dental Halogen Light-Cure Unit (min. 500 mW/cm2): 20 sec. (each side)
  LED Curing Light (min. 1000 mW/cm2): 20 sec. (each side)
- Light Oven: min. 90 seconds
- 4. If required, after light-curing, clean the surface with alcohol and water. The surface will shine with a high gloss.

Note: Close bottle immediately after use.

# CONTRAINDICATIONS:

Glisten is free of methylmethacrylate. Do not use with patients with known allergies to methacrylates. In case of an allergic reaction, please contact a physician.

# WARNINGS:

Glisten is flammable. Avoid sources of ignition and do not store in direct sunlight. In case of contact with oral tissue or skin, flush immediately with water. In case of contact with eyes, flush immediately with water and seek medical attention.

# STORAGE:

Store Glisten protected from light. Do not store above 25°C/78°F. Do not use after expiry date.

KEEP AWAY FROM CHILDREN.

# FOR PROFESSIONAL DENTAL APPLICATION ONLY.

# WARRANTY:

Clinician's Choice Dental Products warrants this product will be free from defects in material and manufacture. Clinician's Choice Dental Products makes no other warranties including any implied warranty of merchantability of fitness for a particular purpose. User is responsible for determining the suitability of the product for the user's application. If this product is defective within the warranty period, your exclusive remedy and Clinician's Choice Dental Products' sole obligation shall be repair or replacement of the product.

# LIMIT OF LIABILITY:

Except where prohibited by law, Clinician's Choice Dental Products will not be liable for any loss or damage arising from this product – whether direct, indirect, special, incidental or consequential, regardless of the theory asserted, including warranty, contract, negligence or strict liability.



# **Glisten**<sup>™</sup> Provisional Resin Glaze



Distributed by Clinician's Choice, a division of Den-Mat Holdings, LLC 1017 W. Central Avenue, Lompoc, CA 93436 USA 800.433.6628 clinicianschoice.com



800.433.6628 www.clinicianschoice.com



# SAFETY DATA SHEET

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade Name: Glisten" Provisional Resin Glaze Use of the Preparation: Varnish Details of the Supplier of the Safety Data Sheet: Distributed by Clinician's Choice, a division of Den-Mat Holdings, LLC 1017 W. Central Avenue, Lompoc, CA 93436 USA Emergency Information: For emergencies or product information, please call 800.433.6628 Date of Issue: May 2015

### SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: Classification According to Regulation (EC) No 1272/2008: Flam. Liq. 2, H225 Higly flammable liquid and vapor. Eye Irrit. 2, H319 Causes serious eye irritation. STOT SE 3, H336 May cause drowsiness or dizziness. Information Concerning Particular Hazards for Human and Environment: The product has to be labeled due to calculation procedure for the "General Classification guideline for preparations of the EU" in the latest version. LABEL ELEMENTS Labeling According to Regulation (EC) 1272/2008: Hazard Pictograms



Signal Word Danger Hazard Statements H225 Highly flammable liquid and vapor H319 Causes serious eye irritation H336 May cause drowsiness or dizziness

### Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P305-P251-P338 IF IN EVES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Labeling According to EU Guidelines: Medical devices as defined in Directive 93/42/EEC and which are invasive or

used in direct physical contact with the human body; are exempted from the provisions of Regulation (EC) No. 1272/2008 (CLP/GHS) usually if they are in the finished state and intended for the final user. OTHER HAZARDS

UTHER HAZARDS Results of PBT and vPvB Assessment PBT: not applicable vPvB: not applicable

# SECTION 3: COMPOSITION/INFORMATION

ON INGREDIENTS CHEMICAL CHARACTERIZATION: Description of the Mixture: Light-cure varnish based on multifunctional methacrylates and ethylacetate. Hazardous Components: CAS-No. [141-78-6], EC-No. 2005-500-4 Ethylacetate GHS02, GHS07 H225, H319, H336

# SECTION 4: FIRST-AID MEASURES

General Information: No special measures required. After Skin Contact: Wash with plenty of water and soap. After Inhalation: Fresh air. After Eye Contact: Rinse opened eye for several minutes under running water and consult a doctor.

After Swallowing: Caution if victim vomits. Risk of aspiration. Keep airways free. Consult a physician. Subsequently administer: Activated charcoal (20 – 40 g in 10% slurry). Laxative: Sodium sulfate (1 tablespoon/ ¼L water).

# SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media: CO<sub>2</sub>, powder, water spray. Use extinguishing method and media suitable to surrounding fire. Special Hazards Arising From the Substance or Mixture: No further relevant information available. Pertoptine Equipment Wear soft contained available uncertactive equipment.

Protective Equipment: Wear self-contained respiratory protective equipment.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Do not inhale vapors/aerosols. Avoid substance contact. Ensure supply of fresh air in enclosed rooms. Environmental Precautions: Do not allow to enter drains/surface

water/ground-water.

Methods for Cleaning Up: Absorb with liquid binding material. Clean up affected area. Reference to Other Sections: See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: HANDLING & STORAGE

*Handling:* This product should only be supplied or handled by dentists or dental technicians or upon their instructions.

Precautions For Safe Handling: Observe normal care for working with chemicals. Information About Fire and Explosion Protection: No special measures required. Storage:

Requirements At Storerooms and Containers: Store only in the original containers. Further Information on Storage Conditions: Store in well ventilated place at 15°C/59°F to 25°C/77°F, protected from light. Store away from food. Store tightly closed. Keep away from heat and sources of ignition. Specific End Uses: No further relevant information available.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	With Limits of Va	lues to be Su	pervised	d at the Workplace:
CAS-No.	name	art	value	unit
[141-78-6]	Ethylacetate	TRGS900 or	400 1500	ml/m <sup>3</sup> mg/m <sup>3</sup>

Additional Information: The lists valid during the making were used as basis. Personal Protective Equipment:

*General Protective and Hygienic Measures:* The usual precautionary measures are to be adhered to when handling chemicals. Keep away from food and beverages. Avoid contact with eyes or skin.

Hand Protection: Protective gloves. Due to missing tests no recommendation to the glove material can be given for the product. Eye Protection: Safety glasses

Respiratory Protection: Required, when aerosols are generated.

SECTION 9: PHYSICAL & CH	IEMICAL F	ROPER	TIES		
INFORMATION ON BASIC PHYSICA	AL AND CHE	MICAL PI	ROPERTIES		
Appearance					
Form: Liquid					
Color: Slightly yellow					
Odor: Sweetish					
Safety Relevant Basic Data	value	unit	method		
Melting Point/Melting Range:	n.a.				
Boiling Point/Boiling Range:	approx. 77	°C			
Flash Point:	-4	°C	DIN 51755		
Ignition Temperature:	No information available				
Danger of Explosion:	Lower limit of explosion 2.1 Vol% Kühn-				
	Upper limit of explosion 11.5 Vol% Birett				
Density:	1,03	(20°C) g	/cm <sup>3</sup>		
Vapor Pressure:	n.d.				
Solubility In/Miscibility With:					
Water:	Soluble				
Content of Solvents:					
Organic Solvents:	Ethylacetate	е			

#### SECTION 10: STABILITY & REACTIVITY

THERMAL DECOMPOSITION/CONDITIONS TO BE AVVIDED Possibility of Hazardous Reactions: no information available Conditions to Avoid: Heat, direct sunlight and radical starters. The product is stable by proper use. Avoid contact with alkali metals, hydrids, strong oxidizing agents, radical intitiators. Hazardous Decomposition Products: No information available.

# SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: (ethylacetate) LD50 (oral, rat) 5600 mg/kg LD50 (otral, rabit) 58000 mg/kg LD50 (inhal., rabit) 58000 mg/kg LD50 (inhal., rat) 5,86 mg/l (8h) Primary Irritation: Skin: Repeated exposure may cause skin dryness or cracking. Eye: Strong irritating effect. Inhalation and Swallowing: Irritation of mucous membranes, loss of appetite, headache, drowsiness. Additional Toxicological Information: Allergic reactions to acrylates after long-term exposure are possible. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us. SAFETY DATA SHEET